



8M


Teilung 8 mm
für Zahnriemenbreite 50 mm




14




16F




18F




19F



19



20



18

Werkstoff: Stahl
Werkstoff: Grauguss (GG)

Beschreibung	Artikelnr.	Typ	Werkstoff	Zähnezahl	Spanbuchsentyp	Bohrung max.	dp	de	Df	Dm	Di	F	L	R	Nr. Bordscheiben	kg
TL 28 8M 50	47050028	16F	St	28	1210	32	71,30	70,08	75	50	60	25	35	312	0,60	
TL 30 8M 50	47050030	16F	St	30	1615	42	76,39	75,13	83	58	60	38	22	314	0,65	
TL 32 8M 50	47050032	16F	St	32	1615	42	81,49	80,16	87	63	60	38	22	315	0,80	
TL 34 8M 50	47050034	16F	St	34	1615	42	86,58	85,21	91	65	60	38	22	316	1,08	
TL 36 8M 50	47050036	16F	St	36	1615	42	91,67	90,30	98	68	60	38	22	319	1,35	
TL 38 8M 50	47050038	16F	St	38	1615	42	96,77	95,39	103	72	60	38	22	320	1,65	
TL 40 8M 50	47050040	18F	St	40	2012	50	101,86	100,49	106	80	60	32	14	321	1,70	
TL 44 8M 50	47050044	18F	St	44	2012	50	112,05	110,67	119	86	60	32	14	325	1,80	
TL 48 8M 50	47050048	18F	St	48	2012	50	122,23	120,86	127	95	60	32	14	327	2,35	
TL 56 8M 50	47050056	18F	St	56	2517	60	142,60	141,23	148	116	60	45	7,5	333	3,35	
TL 64 8M 50	47050064	18F	St	64	2517	60	162,97	161,60	168	136	60	45	7,5	338	4,90	
TL 72 8M 50	47050072	19F	St	72	2517	60	183,35	181,97	192	125	158	60	45	7,5	340	6,90
TL 80 8M 50	47050080	18	GG	80	3020	75	203,72	202,35		180	204	60	51	4,5		8,90
TL 90 8M 50	47050090	19	GG	90	3020	75	229,18	227,81		160	204	60	51	4,5		9,90
TL112 8M 50	47050112	19	GG	112	3020	75	285,21	283,83		170	254	60	51	4,5		12,10
TL144 8M 50	47050144	20	GG	144	3020	75	366,69	365,32		170	336	60	51	4,5		15,40
TL168 8M 50	47050168	14	GG	168	3525	90	427,81	426,44		198	395	60	65	2,5		22,80
TL192 8M 50	47050192	14	GG	192	3525	90	488,92	487,55		198	455	60	65	2,5		26,50