



Passende Kugelhülsen finden Sie auf Seite 402.

Artikelnr.	Ød	ØD	A	H	h	L	E1	E2	Ød1	N1	N2	M	kg
<b>B-KGC27-06</b>	6	12	32	27	13	22	11	23	3,4	9	13	M4	0,04
<b>B-KGC27-08</b>	8	15	32	27	14	24	12	23	3,4	9	13	M4	0,04
<b>B-KGC27-10</b>	10	17	40	33	16	26	13	29	4,3	11	16	M5	0,07
<b>B-KGC27-12</b>	12	19	40	33	17	28	14	29	4,3	11	16	M5	0,07
<b>B-KGC27-14</b>	14	21	40	33	18	28	14	29	4,3	11	16	M5	0,07
<b>B-KGC27-16</b>	16	24	45	38	19	30	15	34	4,3	11	18	M5	0,08
<b>B-KGC27-20</b>	20	28	53	45	23	30	15	40	5,3	13	22	M6	0,12
<b>B-KGC27-25</b>	25	35	62	54	27	40	20	48	6,6	18	26	M8	0,22
<b>B-KGC27-30</b>	30	40	67	60	30	50	25	53	6,6	18	29	M8	0,32
<b>B-KGC27-40</b>	40	52	87	76	39	60	30	69	8,4	22	38	M10	0,61
<b>B-KGC27-50</b>	50	62	103	92	47	70	35	82	10,5	26	46	M12	1,05

- Befestigungsschrauben DIN EN ISO 4762 – 8.8, Federring
- Gewichtsangabe ohne Kugelhülse
- Schmierbohrung M8 x 1