




ZAHNRIEMENRÄDER „PCB“ SYNCHROCHAIN FÜR TAPERBUCHSEN


8M

Teilung 8 mm


für Zahnriemenbreite 12 mm



2F



10F



10

Werkstoff: Stahl

Werkstoff: Grauguss (GG)

| Beschreibung | Artikelnr. | Typ | Werkstoff | Zähnezahl | Spanbuchsentyp | Bohrung max. | dp | de | Df | Dm | Di | F | L | R | d | Nr. Bordscheiben | kg |
|--------------|-------------|-----|-----------|-----------|----------------|--------------|--------|--------|-----|-----|----|----|----|----|-----|------------------|----|
| 8M 22S 12 | PCB47012022 | 2F | St | 22 | | | 56,02 | 54,42 | 60 | 43 | 20 | 30 | 10 | 12 | 308 | 0,43 | |
| TL 8M 25S 12 | PCB47012025 | 10F | St | 25 | 1108 | 28 | 63,66 | 62,06 | 66 | 49 | 20 | 22 | 2 | | 310 | 0,25 | |
| TL 8M 28S 12 | PCB47012028 | 10F | St | 28 | 1108 | 28 | 71,30 | 69,70 | 75 | 56 | 20 | 22 | 2 | | 312 | 0,37 | |
| TL 8M 30S 12 | PCB47012030 | 10F | St | 30 | 1210 | 32 | 76,39 | 74,79 | 83 | 60 | 20 | 25 | 5 | | 314 | 0,41 | |
| TL 8M 32S 12 | PCB47012032 | 10F | St | 32 | 1610 | 42 | 81,49 | 79,89 | 87 | 66 | 20 | 25 | 5 | | 315 | 0,43 | |
| TL 8M 34S 12 | PCB47012034 | 10F | St | 34 | 1610 | 42 | 86,58 | 84,98 | 91 | 68 | 20 | 25 | 5 | | 316 | 0,45 | |
| TL 8M 36S 12 | PCB47012036 | 10F | St | 36 | 1610 | 42 | 91,67 | 90,07 | 98 | 74 | 20 | 25 | 5 | | 319 | 0,59 | |
| TL 8M 38S 12 | PCB47012038 | 10F | St | 38 | 1610 | 42 | 96,77 | 95,17 | 103 | 80 | 20 | 25 | 5 | | 320 | 0,70 | |
| TL 8M 40S 12 | PCB47012040 | 10F | St | 40 | 1610 | 42 | 101,86 | 100,26 | 106 | 85 | 20 | 25 | 5 | | 321 | 0,82 | |
| TL 8M 45S 12 | PCB47012045 | 10F | St | 45 | 2012 | 50 | 114,59 | 112,99 | 119 | 92 | 20 | 32 | 12 | | 325 | 1,10 | |
| TL 8M 48S 12 | PCB47012048 | 10F | St | 48 | 2012 | 50 | 122,23 | 120,63 | 127 | 100 | 20 | 32 | 12 | | 327 | 1,42 | |
| TL 8M 50S 12 | PCB47012050 | 10F | St | 50 | 2012 | 50 | 127,32 | 125,72 | 135 | 104 | 20 | 32 | 12 | | 328 | 1,60 | |
| TL 8M 56S 12 | PCB47012056 | 10F | St | 56 | 2012 | 50 | 142,60 | 141,00 | 148 | 104 | 20 | 32 | 12 | | 333 | 2,10 | |
| TL 8M 60S 12 | PCB47012060 | 10F | St | 60 | 2012 | 50 | 152,79 | 151,19 | 158 | 111 | 20 | 32 | 12 | | 335 | 2,40 | |
| TL 8M 64S 12 | PCB47012064 | 10F | St | 64 | 2012 | 50 | 162,97 | 161,37 | 168 | 111 | 20 | 32 | 12 | | 338 | 2,70 | |
| TL 8M 75S 12 | PCB47012075 | 10 | GG | 75 | 2012 | 50 | 190,99 | 189,39 | | 111 | 20 | 32 | 12 | | | 3,70 | |
| TL 8M 80S 12 | PCB47012080 | 10 | GG | 80 | 2012 | 50 | 203,72 | 202,12 | | 111 | 20 | 32 | 12 | | | 4,40 | |
| TL 8M 90S 12 | PCB47012090 | 10 | GG | 90 | 2012 | 50 | 229,18 | 227,58 | | 111 | 20 | 32 | 12 | | | 5,50 | |